











PRODUCT DESCRIPTION

The advanced technology of the new SEGO modular lightbox system combines innovation with intuition. Toolless down to its feet, SEGO is designed to help heighten your display experience. Magnetic electrical connectors light up the UL certified LED lights that come pre-installed in the profiles. Electrical wires stay hidden from view. Edge-to-edge customizable SEG backlit fabric graphics cover the front and back of the aluminum frame. Portable, configurable, desirable, SEGO is a lightbox unlike the others. SEGO is so well thought out, even its durable foam cut carry bag is made distinctly to keep all parts and pieces protected and organized.

39"W x 39"H x 16.5"D
39.625"W x 39.75"H
40.5" W × 11.75" D × .6"H
11 lbs

GRAPHIC MATERIAL

Dye Sub Backlit Fabric

GRAPHIC FINISHING

Silicone beading sewn onto edge of graphic

DISPLAY CONSTRUCTION

Aluminum extrusion frame with plastic components

SHIPPING WEIGHTS & DIMENSIONS

Shipping Weight	28.5 lbs (frame only) 30.5 lbs (frame & graphic)
Shipping Dimensions	45.5"W x 15.5"H x 6.75"D

GRAPHIC TURN AROUND TIME

2 business days after proof approval (up to 6 sets)

AVAILABILITY CA

LED LIGHT SPECIFICATION		LUMENS		
	BRAND	Osram	VOLTAGE (V)	24
	POWER	3W	POWER (W)	45
	CCT (COLOR TEMP)	6800k	LM/W	130
	AVERAGE BEAM ANGEL	20 °	TOTAL LM	5850
	LM/W	130	AVG LM	5850
	AVG LM/M ²	4800-5800	CU	.8
	VOLTAGE INPUT	24V	EAV	4680
	TRANSFORMER SPECIFIC	CATION		'
	POWER RATE 2	95W, 252W		
	TRANSFORMERS			
	CERTIFICATES	UL, CE, GEM		
	VOLTAGE INPUT	100-240V		













TOOL FREE ASSEMBLY

MAGNETIC WIRE CONNECTION

WOODEN COUNTERTOP

VOLTAGE OUTPUT 24V

TOOL FREE FOOT CONNECTION